www.ventilation-system.com

MV 120 J MV 150 VJ Series



Application

- Decoration of supply and exhaust vents of public, residential and industrial ventilation
- External wall mounting.

Design

- Made of quality and durable plastic.
- Multi-element structure.
- Fitted with louvre shutters for back flow prevention.
- Screw fixing.

Colour modifications



Modifications

MV 120 J - basic model with gravity louvre shutters (J)



- Exhaust grille for wall mounting.
- Fitted with louvre shutters for back flow prevention.



MV 120 VJ, MV 150 VJ - models with a round flange and 'ouviesh terr (VJ)



- Exhaust grille for wall mounting.
- Fitted with louvre shutters.
- Fitted with a round corme sing the ge for mounting with Ø 125 mm air duct (MV 120 J) and 15' mm a duct (MV 150 VJ).



MV 120 VNJ - model with a fla , with values diameters and louvre shutters (VNJ)



- Exhaus grille for wall mounting.
- Fitted with louvre shutters.
- Fitted with a round connecting flange for mounting with \emptyset 100/110/120/130/150 mm air duct.




Overall dimensions

Model	Dimensions, [mm]						
	□B	□H	L	L1	Flange (D)	Air pass, [m²]	Fig. no.
MV 120 J	186	142	15	_	_	0,016	1, 2
MV 120 VJ	186	142	15	45	125	0,0113	1,3
MV 120 VNJ	186	142	15	115	100,110,120,130,150	0,012	1, 4
MV 150 VJ	186	142	15	50	150	0,0113	1,3










Fig. 4

181